

LED UFO High Bay
LUHB Series

Project:	
Catalog#:	
Approved by:	

Features

- Magnesium alloy heatsink
- Ultra-durable Powder Coat Paint
- Standard Color Black
- Comes standard with a high bay hanging hook. Pendant mount possible using ½" threaded conduit entry on top
- Fixtures includes approx. 1 ft long dimming leads and approx. 6 ft long input power cable stripped at ends.
- Color Temperature: 5000K standard (cool white), other colors available (special order, lead times apply)
- Color Rendering Index (CRI): > 80
- Long LED life; L70 > 50,000 hours
- Rated for Ambient Temperatures between -40°C/-40°F to 50°C/122°F
- Input Voltage: MV: 100 – 277V; 50/60 Hz
- Power Factor (PF) > 0.95
- Total Harmonic Distribution (THD) < 20%
- Dimmable: 0-10Vdc
- Distribution: 120° beam angle standard, 60/70/90° possible with reflector accessory (sold separately)
- UL/cUL Listed
- IP65
- Warranty: 5 years

Applications

- Warehouse
- Auditorium
- Retail Space
- Manufacturing Facility



Ordering Information								
Model Series	CCT	Nominal Input Power	Input Voltage	Dimensions			Comparable to HID	DLC ID
				Diameter (in)	Height (in)	Weight (lbs)		
LUHB LED UFO High Bay	50 5000K	A: 100W, 13,000 Lm	MV 100-277V, 50/60 Hz	9.65	7.25	5.0	320W	PLP3GHIFNXB1
		B: 150W, 19,500 Lm		11.00	7.95	7.5	400W	PLQTEGWWRBV2
		C: 200W, 26,000 Lm		11.81	8.15	8.7	750W	PLMVIOM53WE5

Accessories



LUHB-ALR-60
60° Aluminum Reflector
Φ 14" x 5.9" Deep




LUHB-ALR-90
90° Aluminum Reflector
Φ 14" x 6" Deep




LUHB-PCR-70
70° Polycarbonate Reflector
Φ 16" x 10.5" Deep


Photometrics




60° Reflector



70° Reflector



90° Reflector



120°, Standard/no Reflector